Current Sensing Resistors

Wayon Electronics Co., Ltd.
No.1001, Shiwan 7th Road, Pudong, Shanghai 201202, P.R.China
Tel: 86-21-50968309 Fax: 86-21-50968310
E-mail: market@way-on.com *Http://www.way-on.com*

1. SCOPE


This specification is applicable to lead free and halogen free of RoHS directive for MLR series metal alloy low-resistance resistor.

2. Type Designation


MLR	1206	10	F	R001
Product Type	Size（Inch）	Rated Power	Tolerance	Resistance
MLR	1206	1.0W	±1%	1.0mΩ

3. Construction and Physical Dimensions

3.1 Construction



3.2 Physical Dimensions



Type	Dimensions（mm）			
	L	W	H	T1
MLR120610FR001	3.20±0.25	1.60±0.25	0.40±0.10	1.10±0.35


4. Product Specifications

Type	Max.Rating Power（W）	Resistance Value（mΩ）	Resistance Tolerance	T.C.R（PPM/℃）	Operation Temp. Range（℃）
MLR120610FR001	1.0	1.0	±1%	±75	-55~ + 155


Wayon Electronics Co., Ltd.
No.1001, Shiwan 7th Road, Pudong, Shanghai 201202, P.R.China
Tel: 86-21-50968309 Fax: 86-21-50968310
E-mail: market@way-on.com *Http://www.way-on.com*

5. Recommended Customer Soldering Parameters

5.1 Recommended IR Reflow Profile：




5.2 Recommend Solder Pad Layout



Type	a（mm）	b（mm）	i（mm）
MLR120610FR001	1.63	1.70	0.60


5.3 Recommend Steel Net Layout



Type	c（mm）	d（mm）	e（mm）	h（mm）
MLR120610FR001	1.04	1.70	0.70	0.08

Wayon Electronics Co., Ltd.
No.1001, Shiwan 7th Road, Pudong, Shanghai 201202, P.R.China
Tel: 86-21-50968309 Fax: 86-21-50968310
E-mail: market@way-on.com Http://www.way-on.com

6. Power Derating Curve



7. Rating Current

The following equation may be used to determine the DC (Direct Current) or AC (Alternating Current) (RMS, root mean square value) of normal rated power. However, if the result value exceeds the highest current of regulated standards (paragraph 5), the highest normal rated power is to be used

$$\mathbf{I} = \sqrt{P/R}$$

I= Rating current (A)
P= Rating Power (W)
R= Resistance(Ω)

8. Reliability Performance


NO.	Item	Test Condition	Specification
1	Temperature Coefficient of Resistance （T.C.R）	T.C.R. (ppm/°C) $=\frac{(R2-R1)}{R1(T2-T1)}\times 10^6$ R1: resistance at room temperature (T1) R2: resistance at 125°C (T2)	Refer to Electrical Specification
2	Short Time Overload	2.5 times of rated power for 5 sec	△R：±1%
3	High Temperature Exposure	+ 155°C±2°C for 1000hrs	△R：±1%
4	Low Temperature Storage	-55°C±2°C for 1000hrs	△R：±1%
5	Load Life	Apply rated power at 70±2°C for 1000 hours with 1.5hrs ON and 0.5hrs off	△R：±1%
6	Soldering Heat	260±5°C for 10±1 sec	△R：±1%
7	Temperature Cycling	-55°C to +155°C，100cycles	△R：±1%
8	Solderability	245±5°C for 3±0.5 sec	Covered area ＞95%
9	Bending Strength	Chips mounted on a 90mm PCB(FR4) 2 mm bending Bending time: 60±1 seconds	△R：±1%

Current Sensing Resistors

Wayon Electronics Co., Ltd.
No.1001, Shiwan 7th Road, Pudong, Shanghai 201202, P.R.China
Tel: 86-21-50968309 Fax: 86-21-50968310
E-mail: market@way-on.com *Http://www.way-on.com*


9. Packaging Information

9.1 Reel Dimensions



Type	ΦD （mm）	W（mm）	ΦM（mm）
MLR120610FR001	60±2	9.0±1	178±5

9.2 Carrier Dimensions(mm)



Type	W	P	E	F	ΦD0	ΦD1
MLR120610FR001	8.0±0.30	4.0±0.10	1.75±0.10	3.5±0.10	1.5 + 0.10	0.6±0.05
	G	H	A	B	T	
	4.0±0.10	2.0±0.10	2.05±0.20	3.65±0.20	0.60±0.20	

9.3 Peeling Strength of Top Cover Tape

Peeling Strength：0.1-1.0N at a peel-off speed of 300 mm/min.

9.4 Packaging

TYPE	PCS/Reel
MLR120610FR001	5,000

10. Storage Temperature and Life

Temperature：5~35ºC, Humidity：≤80%

When the product is finally discarded, it can be treated as general electronic waste, and raw material compositions of CSR can be referred to MSDS.