
WM02P18F

P-Channel Enhancement MOSFET

Features

- Way-on Small Signal MOSFETs
- V_{DS}= -20V, I_D = -1.8A
  Typ. $R_{DS(on)}$ = 112mΩ @ V_{GS} = -4.5V
  Typ. $R_{DS(on)}$ = 149mΩ @ V_{GS} = -2.5V
- Trench LV MOSFET Technology




DFN1006-3L


Mechanical Characteristics

- DFN1006-3L Package
- Marking: Making Code
- RoHS Compliant & Halogen-Free

Schematic & PIN Configuration



Device symbol



DFN1006-3L(Top View)

Absolute Maximum Rating (T_A=25°C unless otherwise noted)

Rating		Symbol	Value	Units
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±10	V
Continuous Drain Current	T_A=25°C	I_D	-1.8	A
Pulsed Drain Current[1]		I_{DM}	-7.2	A
Power Dissipation	T_A=25°C	P_D	0.7	W
Junction and Storage Temperature Range		T_J ,T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Ambient[2]	$R_{\theta JA}$	179	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}= 0V, I_D= -250μA	-20	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}= -20V, V_{GS}= 0V	-	-	-1	μA
Gate-Source Leakage	I_{GSS}	V_{DS}= 0V, V_{GS}= ±10V	-	-	±100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D= -250μA	-0.4	-	-1.0	V
Drain-Source on-State Resistance[3]	$R_{DS(on)}$	V_{GS}= -4.5V, I_D= -1.7A	-	112	150	mΩ
		V_{GS}= -2.5V, I_D= -1.2A	-	149	210	
		V_{GS}= -1.8V, I_D= -1.0A	-	207	290	
Dynamic Characteristics[4]						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -10V, f=1MHz	-	168	-	pF
Output Capacitance	C_{oss}		-	30	-	
Reverse Transfer Capacitance	C_{rss}		-	24	-	
Switching Characteristics[4]						
Total Gate Charge	Q_g	V_{GS} = -4.5V, V_{DS}= -10V, I_D= -1.7A	-	2.72	-	nC
Gate−Source Charge	Q_{gs}		-	0.49	-	
Gate−Drain Charge	Q_{gd}		-	0.57	-	
Turn-On Delay Time	$t_{d(on)}$	V_{GS} = -4.5V, V_{DD} = -10V, R_G = 3Ω, I_D = -1.7A	-	6.5	-	ns
Rise Time	t_r		-	4.8	-	
Turn-Off Delay Time	$t_{d(off)}$		-	18	-	
Fall Time	t_f		-	5	-	
Drain-Source Body Diode Characteristics						
Diode Forward Voltage[3]	V_{SD}	I_S = -1A, V_{GS} = 0V	-	-	-1.2	V
Continuous Source Current	I_S	-	-	-	-1.8	A

Notes:

1. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C.

2. The data tested by surface mounted on a 1 inch2 FR-4 board with 2OZ copper, The value in any given application depends on the user's specific board design.

3. Pulse Test: Pulse width≤300μs, duty cycle≤2%.

4. This value is guaranteed by design hence it is not included in the production test.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Forward Characteristics of Reverse




Figure 4. $R_{DS(ON)}$ vs. V_{GS}




Figure 5. $R_{DS(ON)}$ vs. I_D




Figure 6. Normalized RDS(on) vs. Temperature




Figure 7. Capacitance Characteristics





Figure 8. Gate Charge Characteristics

Outline Drawing – DFN1006-3L







DFN1006-3L

DIMENSIONS				
SYMBOL	MILLIMETER		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	0.45	0.55	0.018	0.022
A1	0.00	0.05	0.000	0.002
b	0.40	0.60	0.016	0.024
b1	0.10	0.20	0.004	0.008
D	0.95	1.05	0.037	0.041
e	0.65BSC		0.026BSC	
E	0.55	0.65	0.022	0.026
E1	0.19BSC		0.007BSC	
L	0.20	0.30	0.008	0.012

Land Pattern



Marking Codes

Part Number	WM02P18F
Marking Code	

Package Information

Qty：10k/Reel

CONTACT INFORMATION

No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**
For additional information, please contact your local Sales Representative.

WAYON ® is registered trademark of Wayon Corporation.

Product Specification Statement

1. The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

2. The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.

3. WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

4. Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

5. The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.

6. Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.