
BT132 Series


Silicon Controlled Rectifier

Features


- Blocking Voltage to 800V
- High dV/dt Rate
- $I_{T(RMS)}$ to 2A of Triacs
- RoHS Compliant & HF



SOT-223-3L




SOT-223-2L



TO-220F(Ins)

Pin Configuration



Absolute Maximum Ratings（Tc=25℃ Unless otherwise specified）

Parameter	Symbol	Value	Unit
Storage temperature range	T_{stg}	-40~150	℃
Operating junction temperature range	T_j	-40~125	℃
Repetitive peak off-state voltage (T_j=25℃)	V_{DRM}	800	V
Repetitive peak reverse voltage (T_j=25℃)	V_{RRM}	800	V
RMS on-state current	$I_{T(RMS)}$	2	A
Non repetitive surge peak on-state current (full cycle, F=50Hz)	I_{TSM}	16	A
I^2t value for fusing (tp=10ms)	I^2t	1.28	A^2s
Critical rate of rise of on-state current (I_G=2×I_{GT})	dI/dt	50	A/μs
Peak gate current	I_{GM}	1	A
Peak gate power	P_{GM}	5	W
Average gate power dissipation	$P_{G(AV)}$	0.5	W
Thermal Resistance(between Junction and Case) @SOT-223-3L/SOT-223-2L	$R_{th(J-C)}$	18（Typ.）	℃/W
Thermal Resistance(between Junction and Case) @TO-220F(Ins）	$R_{th(J-C)}$	4.5（Typ.）	℃/W

Electronics Characteristics（Tc=25℃ Unless otherwise specified）-3Quadrants：

Parameter	Symbol	Quadrant		Value		Unit
				TW	SW	
Gate Trigger Current (Continuous dc)@V_D=12V, R_L=33Ω	I_{GT}	Ⅰ-Ⅱ-Ⅲ	Max	5	10	mA
Gate Trigger Voltage (Continuous dc) @V_D=12V, R_L=33Ω	V_{GT}	ALL		1.3		V
Gate non-trigger voltage@V_D=V_{DRM}	V_{GD}	ALL	Min	0.2		V
Holding Current@I_T=100mA	I_H	-	Max	10	15	mA
Latching Current@I_G=1.2I_{GT}	I_L	Ⅰ-Ⅲ	Max	15	30	mA
		Ⅱ		20	40	
Critical Rate of Rise of Off State Voltage @V_D=0.67×V_{DRM}, T_j=125℃,Gate Open	dV/dt	-	Min	100	200	V/μs
Peak Forward On-State Voltage @I_{TM}=1.5A,tp=380μs, T_j=25℃	V_{TM}	-	Max	1.6		V
Repetitive peak off-state current @V_{DRM}=V_{RRM},T_j=25℃	I_{DRM}	-		5		μA
Reverse Blocking Current @V_{DRM}=V_{RRM},T_j=125℃	I_{RRM}	-		1		mA

Note: The above typical parameters or typical characteristics are only indicative and do not make specific guarantees. If detailed values are required, additional communication and provision are required.

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature




FIG.3: Surge peak on-state current versus number of cycles




FIG.4:On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp<10ms






FIG.6: Relative variations of gate trigger current , holding current and latching current versus junction temperature




Outline Drawing- SOT-223-3L

SYMBOL	MM		
	MIN	NOM	MAX
A	1.40	-	1.95
A1	0.01	-	0.15
B	2.80	3.00	3.20
B1	0.60	-	0.84
C	0.20	0.26	0.37
D	6.20	6.50	6.95
E	3.30	3.50	3.70
F	-	4.60	-
F1	-	2.30	-
G	0.60	-	1.20
H	1.50	1.75	2.00
J	6.65	7.00	7.30
K	-	0.90	-




Outline Drawing- SOT-223-2L

SYMBOL	MM		
	MIN	NOM	MAX
A	1.40	-	1.95
A1	0.01	-	0.15
B	2.80	3.00	3.20
B1	0.60	-	0.84
C	0.20	0.26	0.37
D	6.20	6.50	6.95
E	3.30	3.50	3.70
F	-	4.60	-
F1	-	2.30	-
G	0.60	-	1.20
H	1.50	1.75	2.00
J	6.65	7.00	7.30
K	-	0.90	-
L	0	0.10	0.80




Outline Drawing- TO-220F（Ins）

SYMBOL	MM		
	MIN	NOM	MAX
A	4.40	-	4.90
B	0.58	0.8	0.90
C	0.40	-	0.75
C2	2.34	-	3.10
C3	2.00	-	3.05
D	8.60	-	9.80
E	9.70	-	10.5
F	6.40	-	7.50
G	-	2.54	-
H	28.0	-	29.8
L1	2.80	-	3.93
L2	1.14	-	1.70
L3	2.65	3.30	3.85
V1	-	45°	-



Marking Code:


For Example:



SOT-223-2L，SOT-223-3L，TO-220F(Ins)

Note: The second line of printed content is the result of removing the package code from the part number system

Part Number System



Package Information

Package	Base qty.	Delivery mode
TO-220F(Ins)	50	Tube
SOT-223-2L	2500	Reel
SOT-223-3L	2500	Reel

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: http://www.way-on.com
For additional information, please contact your local Sales Representative.
WAYON® is registered trademark of Wayon Corporation.

Product Specification Statement

1.The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

2.The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.

3.WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

4.Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

5.The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.

6.Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.