
WS30P10SMB-BNRH

Power Transient Voltage Suppressor

Features

- 1000 watts Peak Pulse Power (10/1000μs)
- Bidirectional Protection
- Fast Response Time : Typically < 1ns
- Excellent Clamping Capability
- Built-in Strain relief
- Low inductance
- Low profile package
- High temperature solder:260℃/10 seconds at terminal



SMB
(JEDEC DO-214AA)

Mechanical Characteristics

- JEDEC DO-214AA package
- Molding compound flammability rating: UL 94V-0
- Marking : See Marking Code
- Packaging : Tape and Reel per EIA 481
- RoHS Compliant

Applications

- I/O Interfaces
- Power lines
- Automotive and Telecommunication
- Computers &Consumer Electronics
- Industrial Electronics

Absolute Maximum Rating


Rating	Symbol	Value	Units
Peak Pulse Power (tp =10/1000μs) (see Note1,2)	P_{PPM}	1000	Watts
Peak pulse current (10/1000μs) (see Note2)	I_{PP}	20.66	A
Non-repetitive peak impulse Voltage (1.2/50-8/20μs, 2Ω)	V_{PPSM}	1000	V
Power Dissipation on infinite heat sink T_L = 50 °C (Fig4)	P_D	6.5	W
Operating Junction Temperature range	T_J	-55 to + 150	℃
Storage Temperature range	T_{STG}	-55 to + 150	℃

Note1: Peak Pulse Power Rating as Pulse Width, per Fig1.

Note2: Peak Pulse Power or Current Derated above T_A=25℃ Per Fig. 2 and Non-Repetitive Current Pulse, Per Fig.3.


©2019 WAYON Corporation

Pin Configuration



Electrical Characteristics

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current



WS30P10SMB-BNRH					
Parameter	**Symbol**	**Conditions**	**Minimum**	**Maximum**	**Units**
Reverse Stand-Off Voltage	V_{RWM}			30	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	32	37	V
Reverse Leakage Current	I_R	V_{RWM}=30V, T=25°C		1	μA
Clamping Voltage	V_C	I_{PP}=20.66A, t_p=10/1000μs		48.4	V
Clamping Voltage	V_C	V_{PPSM}=1000V, tp=1.2/50-8/20μs(2Ω)		45	V

Typical Characteristics

Figure 1: Peak Pulse Power Rating Curve




Figure 2: Pulse Derating Curve




Figure 3: Pulse Waveform






Figure 4: Steady State Power Dissipation Derating Curve




Soldering Parameters

Reflow Condition		
Pre Heat	Temperature Min ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60-190 s
Average ramp up rate (Liquidus Temp) (T_L) to peak		3°C/s max
Ts(max) to TL - Ramp-up Rate		3°C/s max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Temperature (t_L)	60-150 s
Peak Temperature (T_P)		$260^{+0/-5}$ °C
Time within actual peak Temperature (t_p)		20-40 s
Ramp-down Rate		5°C/s max
Time 25°C to peak Temperature (T_P)		8 minutes max
Do not exceed		260°C




Outline Drawing – SMB(DO-214AA)

Ref.（mm）	Millimeters	
	Min.	Max.
A	2.130	2.600
A1	-	0.300
B	1.900	2.200
E	4.100	4.750
E1	5.210	5.590
D	3.300	3.940
L	0.760	1.520




Recommended Solder Pad Layout



Dimensions in mm

Marking Code



Package Information

Package Type	Description	Quantity（pcs）	Standard
SMB(DO-214AA)	Tape & Reel -12mm/13″ tape	3000	EIA-481-D

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**
For additional information, please contact your local Sales Representative.

WAYON ® are registered trademarks of Wayon Corporation.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.