
WS58P30SMC-B3

Power Transient Voltage Suppressor

Features

- Bidirectional Protection
- Fast Response Time : Typically < 1ns
- Excellent Clamping Capability
- Glass Passivated Junction
- Built-in Strain relief
- Low inductance
- Low profile package



Mechanical Characteristics

- SMC-3 package
- Molding compound flammability rating: UL 94V-0
- Packaging : Tape and Reel per EIA 481
- RoHS Compliant

Applications


- I/O Interfaces
- Power lines
- Automotive and Telecommunication
- Computers &Consumer Electronics
- Industrial Electronics

Absolute Maximum Rating			
Rating	**Symbol**	**Value**	**Units**
Peak Pulse Power (10/1000μs)(see Note1,2)	P_{PPM}	3000	Watts
Peak pulse current (10/1000μs)(see Note2)	I_{PP}	32.1	A
Peak pulse current (8/20μs)	I_{PP}	500	A
Peak pulse Voltage(10/700-5/320μs, 40Ω)	V_{PP}	4000	V
Power Dissipation on infinite heat sink T_L = 50 °C (Fig4)	P_D	6.5	W
Operating Junction Temperature range	T_J	-55 to + 150	℃
Storage Temperature range	T_{STG}	-55 to + 150	℃

Note1: Peak Pulse Power Rating as Pulse Width ,per Fig1.


Note2: Peak Pulse Power or Current Derated above T_A=25℃ Per Fig. 2 and Non-Repetitive Current Pulse,Per Fig.3.

Pin Configuration



Electrical Characteristics

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current



WS58P30SMC-B3 (PIN1-2, PIN3-2)					
Parameter	**Symbol**	**Conditions**	**Minimum**	**Maximum**	**Units**
Reverse Stand-Off Voltage	V_{RWM}			58	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	64.4	71.2	V
Reverse Leakage Current	I_R	V_{RWM}=58V, T=25°C		5	μA
Clamping Voltage	V_C	I_{PP}=32.1A, t_p=10/1000μs		93.6	V

Typical Characteristics

Figure 1: Peak Pulse Power Rating Curve




Figure 2: Pulse Derating Curve




Figure 3: Pulse Waveform






Figure 4: Steady State Power Dissipation Derating Curve




Recommended Soldering Parameters

Reflow Condition		
Pre Heat	Temp. Min ($T_{s(min)}$)	150°C
	Temp. Max ($T_{s(max)}$)	200°C
	Time (Min to Max) (t_s)	60-190 s
Average ramp up rate (Liquidus Temp.) (T_L) to peak		3°C/s max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/s max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Temperature (t_L)	60-150 s
Peak Temperature (T_P)		260+0/-5 °C
Time within actual peak Temperature (t_p)		20-40 s
Ramp-down Rate		5°C/s max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		260°C




Outline Drawing – SMC-3

Ref.（mm）	Millimeters	
	Min.	Max.
A	5.49	6.25
B	7.55	8.20
C	2.75	3.25
D	6.60	7.40
E	0.76	1.52
G	-	0.30
H	2.06	2.70
M	0.70	1.30
N	0.80	1.40



Recommended Solder Pad Layout



Dimensions in mm

Marking Code



Package Information

3000Pcs/Reel

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**
For additional information, please contact your local Sales Representative.

WAYON ® are registered trademarks of Wayon Corporation.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.