
BAV3004W-AT

Fast Switching Diode

Features

- Low Leakage Current
- High Reverse Breakdown Voltage
- AEC-Q101 Qualified



SOD-123

Mechanical Data

- SOD-123 package
- Marking: Marking Code
- RoHS Compliant & HF
- Device meets MSL1 requirement

Absolute Maximum Rating

Parameter	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	350	V
Forward Continuous Current	I_F	225	mA
Peak Forward Surge Current@8.3ms Half Sine	I_{FSM}	3	A
Operating and Storage Temperature Range	T_J, T_{stg}	-65 to +150	°C
Power Dissipation	P_D	400	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	312	°C /W


Electrical Characteristics (T_{amb}=25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	V_{BR}	I_R = 100μA	350	-	-	V
Reverse Leakage Current	I_R	V_R = 240V, T_J=25℃	-	-	100	nA
		V_R = 240V, T_J=150℃			100	μA
Forward Voltage	V_F	I_F = 20mA	-	-	1.00	V
		I_F = 100mA	-	-	1.20	
		I_F = 200mA			1.25	

©2023 WAYON Corporation


Soldering Parameters

Reflow Condition		Pb – Free assembly
Pre Heat	Temperature Min ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (ts)	60 – 190 secs
Average ramp up rate (Liquidus Temp) (T_L) to peak		5°C/second max
$T_{S(max)}$ to T_L——Ramp-up Rate		5°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_P)		260+0/-5 °C
Time within actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		5°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		280°C




Tape And Reel Information


Reel Dimensions



Tape Dimensions




Quadrant Assignments For PIN1 Orientation In Tape




RD	Reel Dimensions	7 inch
W	Overall width of the carrier tape	8 mm
P1	Pitch between successive cavity centers	4mm

Outline Drawing –SOD-123

PACKAGE OUTLINE






SOD-123

DIMENSIONS

SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.450	0.650	0.018	0.026
c	0.080	0.150	0.003	0.006
D	1.500	1.700	0.059	0.067
E	2.600	2.800	0.102	0.110
E1	3.550	3.850	0.140	0.152
L	0.500 REF		0.020 REF	
L1	0.250	0.450	0.010	0.018
θ	0°	8°	0°	8°



DIMENSIONS: MILLIMETERS

Notes

1. Controlling Dimensions in Millimeters.
2. Dimensions are exclusive of mold flash and metal burrs.

Marking Codes

Part Number	BAV3004W-AT
Marking Code	4W

Package Information

Qty：3k/Reel

CONTACT INFORMATION

No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**
For additional information, please contact your local Sales Representative.

WAYON ® is registered trademark of Wayon Corporation.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.