# MLR120610FR003

Current Sensing Resistor

## 1. SCOPE


- This specification is applicable to lead free and halogen free of RoHS directive for MLR series metal alloy low-resistance resistor.

## 2. Type Designation


| MLR | 1206 | 10 | F | R003 |
|---|---|---|---|---|
| **Product Type** | **Size（Inch）** | **Rated Power** | **Tolerance** | **Resistance** |
| MLR | 1206 | 1.00W | ±1% | 3.0mΩ |

## 3. Construction and Physical Dimensions

### 3.1 Construction




### 3.2 Physical Dimensions





| Type | Dimensions（mm） | | | |
|---|---|---|---|---|
| | L | W | H | T1 |
| MLR120610FR003 | 3.20±0.25 | 1.60±0.25 | 0.40±0.10 | 0.85±0.35 |

## 4. Product Specifications


| Type | Max. Rating Power（W） | Resistance Range（mΩ） | Resistance Tolerance | T.C.R（PPM/°C） | Operation Temp. Range（°C） |
|---|---|---|---|---|---|
| MLR120610FR003 | 1.0 | 3.0 | ±1% | ±75 | -55~ + 155 |

## 5. Recommended Customer Soldering Parameters

### 5.1 Recommended IR Reflow Profile





### 5.2 Recommend Solder Pad Layout





| Type | a（mm） | b（mm） | i（mm） |
|---|---|---|---|
| MLR120610FR003 | 1.35 | 1.70 | 1.20 |

### 5.3 Recommend Steel Net Layout




| Type | c（mm） | d（mm） | e（mm） | h（mm） |
|---|---|---|---|---|
| MLR120610FR003 | 0.85 | 1.53 | 1.30 | 0.08 |

## 6. Power Derating Curve




## 7. Rating Current

The following equation may be used to determine the DC (Direct Current) or AC (Alternating Current) (RMS, root mean square value) of normal rated power. However, if the result value exceeds the highest current of regulated standards, the highest normal rated power is to be used.

$$\mathbf{I} = \sqrt{P/R}$$

I= Rating current (A)

P= Rating Power (W)


R= Resistance(Ω)

## 8. Reliability Performance

| NO. | Item | Test Method | Test Condition | Specification |
|---|---|---|---|---|
| 1 | Temperature Coefficient of Resistance （T.C.R） | JIS C 5201-1 clause 4.8 | T.C.R. (ppm/°C) $=\frac{(R2-R1)}{R1(T2-T1)}\times 10^6$<br>R1: resistance at room temperature (T1)<br>R2: resistance at 125°C (T2) | Refer to Electrical Specification |
| 2 | Short Time Overload | JIS C 5201-1 clause 4.13 | 2.5 times of rated power for 5 sec | △R：±1% |
| 3 | High Temperature Exposure | JIS C 5201-1 clause 4.23.2 | ﹢155°C±2°C for 1000hrs | △R：±1% |
| 4 | Low Temperature Storage | JIS C 5201-1 clause 4.23.4 | -55°C±2°C for 1000hrs | △R：±1% |
| 5 | Load Life | JIS C 5201-1 clause 4.25 | Apply rated power at 70±2°C for 1000 hours with 1.5hrs ON and 0.5hrs off | △R：±1% |
| 6 | Soldering Heat | JIS C 5201-1 clause 4.18 | 260±5°C for 10±1 sec | △R：±1% |
| 7 | Temperature Cycling | JIS C 5201-1 clause 4.19 | -55°C to +155°C，100cycles | △R：±1% |
| 8 | Solderability | JIS C 5201-1 clause 4.17 | 245±5°C for 3±0.5 sec | Covered area ＞ 95% |
| 9 | Bending Strength | JIS C 5201-1 clause 4.33 | Chips mounted on a 90mm PCB(FR4)<br>2 mm bending<br>Bending time: 60±1 seconds | △R：±1% |


## 9. Packaging Information

### 9.1 Reel Dimensions




| Type | ΦD （mm） | W（mm） | ΦM（mm） |
|---|---|---|---|
| MLR120610FR003 | 60±2 | 9.0±1 | 178±5 |

### 9.2 Carrier Dimensions (mm)




| Type | W | P | E | F | ΦD0 | ΦD1 |
|---|---|---|---|---|---|---|
| MLR120610FR003 | 8.0±0.10 | 4.0±0.10 | 1.75±0.10 | 3.5±0.10 | 1.5+0.10 | 1.0±0.10 |
| | G | H | A | B | T | |
| | 4.0±0.10 | 2.0±0.10 | 1.75±0.10 | 3.35±0.10 | 0.55±0.10 | |

### 9.3 Peeling Strength of Top Cover Tape

Peeling Strength：0.1-1.0N at a peel-off speed of 300 mm/min.

### 9.4 Packaging

| TYPE | PCS/Reel |
|---|---|
| MLR120610FR003 | 5,000 |

## 10. Storage Temperature And Life

Temperature：5~35°C, Humidity：≤80%.

When the product is finally discarded, it can be treated as general electronic waste, and raw material compositions of CSR can be referred to MSDS.

## Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: http://www.way-on.com

For additional information, please contact your local Sales Representative.

WAYON® is registered trademark of Wayon Corporation.

## Product Specification Statement

1.The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

2.The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.

3.WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

4.Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

5.The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.

6.Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.