
WAYON

WD3K8xx

GLASS PASSIVATED BRIDGE RECTIFIERE

Features





- Low forward voltage drop，high current capability
- Ideal for printed circuit board
- Forward Current - 8.0Amperes
- Thin single in-line package
- MSL: Level 1
- Mounting postition:Any
- Epoxy meets UL 94 V-0 flammability rating

Mechanical Data

- Case: D3K Package

Absolute Maximum Ratings and Electronics characteristics

Ratings@25℃ ambient temperature unless otherwise specified

Parameter		Symbol	WD3K 8005	WD3K 801	WD3K 802	WD3K 804	WD3K 806	WD3K 808	WD3K 810	UNITS
Maximum repetitive peak reverse voltage		V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage		V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage		V_{DC}	50	100	200	400	600	800	1000	V
Average forward rectified current T_C=100℃		$I_{F(AV)}$	8.0							A
Peak forward surge current 8.3ms single half. Sine Wave Superimposed on Rated Load		I_{FSM}	175							A
Maximum instantaneous forward voltage at I_F=8A,TJ=25℃		V_F	1.1							V
Maximum DC reverse current (TJ= 25℃)at rated DC blocking voltage	TJ= 25℃	I_R	5							μA
	TJ= 125℃	I_R	200							μA
Typical Junction Capacitance at VR=4V, f=1MHz		C_j	50							pF
I^2t Rating for fusing (t<8.3ms)		I^2t	127							A^2S
Typical Thermal Resistance (NOET1)		$R_{\theta JC}$	5.0							℃/W
Operating and Storage temperature range		T_J,Tstg	-55 ~ +150							℃

Notes：

1..Junction to case with heatsink.

Ratings and Characteristic Curves (TA=25℃ unless otherwise note)

Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Capability






Fig.4 Typical Reverse Characteristics



Note: The above typical parameters or typical characteristics are only indicative and do not make specific guarantees. If detailed values are required, additional communication and provision are required.

Product Dimensions



Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.531	0.555	13.5	14.1
B	0.413	0.437	10.5	11.1
C	0.500	0.539	12.7	13.7
D	0.138	0.162	3.51	4.11
E	0.026	0.034	0.66	0.86
F	0.043	0.059	1.1	1.5
G	0.264	0.287	6.7	7.3
H	0.114	0.130	2.9	3.3
I	0.122	0.134	3.1	3.4
J	0.079	0.091	2.0	2.3
K	0.016	0.024	0.4	0.6

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207
Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com
WAYON website: **http://www.way-on.com**
For additional information, please contact your local Sales Representative.

WAYON ® is registered trademarks of Wayon Corporation.

Product Specification Statement

The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. WAYON shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and WAYON assumes no responsibility for the application of the product.

WAYON strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, WAYON cannot guarantee that the information provided in the product specification is entirely accurate and error-free. WAYON shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications. WAYON reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with WAYON to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult WAYON in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

Users are advised to pay attention to the parameter limit values specified in the product specification and maintain a certain margin in design or application to ensure that the product does not exceed the parameter limit values defined in the product specification. This precaution should be taken to avoid exceeding one or more of the limit values, which may result in permanent irreversible damage to the product, ultimately affecting the quality and reliability of the system or equipment.

The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. WAYON shall assume no responsibility for any consequences resulting from such usage.

Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. WAYON shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.